



05000PS Motor Oil 0W-40 Premium Synthetic PS

Document version: Jul 15, 2024



Description

This premium synthetic "MID SAPS" engine oil has been developed for use in high-performance gasoline and diesel engines. The excellent fluidity at low temperatures ensures perfect lubrication even before the engine reaches operating temperatures. Combined with its cleaning properties, this results in superior protection against wear. This engine oil is suitable for various high-performance engines, including Porsche, Lamborghini, VAG group, Bentley, Mercedes and Lotus where a 0W-40 viscosity with these specifications is required.

Application manual

According to the specifications of

ACEA C3
API SN / SN Plus / SP
MB-Approval 229.51 / 229.52
Porsche C40
VW 511.00

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001PS	1 L	6	450
05005PS	5 L	4	112
05020PS	20 L	1	30
05060PS	60 L	1	6
05205PS	205 L	1	2
05999PS	1000 L	1	-
P05000PS	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.846	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	67.9	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	13.4	mm ² /s	ASTM D445
Viscosity Index	204		ASTM D2270
Flashpoint COC	218	°C	ASTM D92
Pourpoint	-48	°C	ASTM D97
Total Base Number	9.4	mgKOH/g	ASTM D2986
Sulphated Ash	0.77	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.